

## Pirlo Tubes sample F-PO 240 $\mu m$ white "Pirlo CHALK BARE"

BASE MATERIAL	PE/chalk compound, white Chalk percentage > 50 % Strenght: 240 μm	
MATERIAL COMPOSITE	Blocked blown film	
TUBE DIAMETERS	30 mm, 35 mm & 40 mm	
WELDING	Decoseam	
CLOSURE	Flip-top cap for tubes in diameters 35 mm and 40 mm (customer-specific colours; different orifices)	Screw cap M15 and S13 for tubes in diameter 35 mm and M15 in diameter 30 mm
PRINTING	High-resolution, photorealistic digital print (digital Off-Set)  → Individualization and personalization available	
SURFACE FINISH	Glossy laminated (OPP), strength 24 μm or Matt laminated (OPP), strength 27 μm	
ADVANTAGES	<ul> <li>Soft-touch paper-like feel</li> <li>"Used looked" optics through the use</li> <li>Nearly invisible seam allows 360° print design</li> <li>Sustainability:         <ul> <li>reduced CO<sub>2</sub> footprint in the film material</li> <li>less material (reduced wall thickness)</li> <li>residual emptying</li> </ul> </li> <li>Recycability confirmed by the institut cyclos-HTP</li> </ul>	

